



Comparison of Discrete Wavelet Transform (DWT), Discrete Cosine Transform (DCT) and Stationary Wavelet Transform (SWT) based Satellite Image Fusion Techniques

Ch Ramesh Babu¹, D. Srinivasa Rao²

¹CSE, GCET, Hyderabad, India; ²IT, VNRVJIT, Hyderabad, India.

ABSTRACT

The aim of the image fusion is to combining evidence from different images; Multispectral (MS) and Panchromatic (PAN) images acquired from different sensors of the same interpretation in directive to convey enhanced spectral and spatial information as well. In this paper discrete wavelet transform (DWT) and two specializations of discrete cosine transform (DCT); i) DCT variance, ii) consistency verification with DCT variance fusion techniques are implemented and compared with the proposed methodology for image fusion named stationary wavelet transform (SWT). Fused results obtained from these fusion approaches are assessed through typical evaluation parameters. Fused outcomes obtained from proposed SWT outperforms DWT and two flavors of DCT based fusion approaches. The shift invariant property of SWT produces improved spectral and spatial evidence in the fused image followed by fused grades accomplished from DCT based fusion approaches. The discrete cosine transforms (DCT) grounded approaches of image fusion are further proper and performance oriented in real time applications by means of DCT founded principles of static images. Conclusion through this work is a glowing systematic practice for fusion of multi-focus images based on SWT is presented and proved that SWT based fused results surpass other fusion approaches.

Key Words: DWT, DCT, SWT, Variance, Consistency verification

INTRODUCTION

Multisensor image fusion is the method of conjoining significant evidence from two or more images addicted to a one image. The resultant image determined as an additional useful information than at all of the participated images. In remote sensing solicitations, the accumulative obtainability of planetary accepted sensors provides a inspiration for various image fusion procedures. Numerous conditions in image processing need great spatial and extraordinary spectral information in a particular image. Furthermost of the obtainable utensils is not proficient of producing such information influentially. Image fusion methods permit the combination of altered evidence foundations. The output image from fusion may obligate harmonizing dimensional and supernatural information features. However, the average image fusion pro-

cedures can change the spectral evidence of the multispectral data while combining input images through fusion process.

[1] grants two elementary fusion areas, explicitly spatial domain and transform domain. Principal component analysis (PCA) which is dimensional province technique and discrete cosine transform (DCT), discrete wavelet transform (DWT), stationary wavelet transform (SWT), non-sub sampled contourlet transform (NSCT), and complex contourlet transform (CCT) which are transform domain procedures. Enactment-measures are executed to assess and authenticate the enactment of image fusion procedure. Investigational outcomes direct that the image fusion technique founded on complex contourlet transform (CCT) is improved than former approaches.

Corresponding Author:

Ch Ramesh Babu, CSE, GCET, Hyderabad, India;
Email: chramesh522@gmail.com

ISSN: 2231-2196 (Print)

ISSN: 0975-5241 (Online)

DOI: <http://dx.doi.org/10.7324/IJCRR.2017.9129>

Received: 02.05.2017

Revised: 16.05.2017

Accepted: 30.05.2017

[2] benevolences two methodologies for the image fusion, viz. spatial fusion and renovate fusion and nearby are practices for instance principal component analysis (PCA) which is dimensionl province and discrete wavelet transform (DWT), stationary wavelet transform (SWT) and discrete cosine transform (DCT) which are transmute domain procedures. Contrast among PCA, DWT, DCT with SWT is done. along with parameter like, spatial frequency (SF), standard derivation (SD), PSNR, NCC, etc.

[3] described procedures for image fusion using stationary wavelet transform (SWT) with the assistance of intuitionistic fuzzy set (IFS) processes. In IFS, fewer number of factors is actually suitable for computing membership importance. On the supplementary, SWT has shift invariance capability above the DWT. Deliberated SWT founded image fusion procedures with numerous IFS processes for dissimilar data set and related the outcomes with separately.

[4] Numerous conventional multi-focus image fusion procedures and some unusual multi-focus image fusion procedures are discussed and recommended the R-FCM (Rough-Fuzzy C-Means) method to improve the multi-focus image fusion approach in dynamic scene.

[5] projected non subsampled contourlet transform based image fusion of multi-sensor satellite images. In the planned effort, interchange among the spectral bias and improvement of spatial evidence is observed while fusing input images. The harms of wavelet grounded fusion procedures for instance partial directivity, deficiency of phase evidence and shift invariant are spoken with the assistance of Non subsampled contourlet transform. The Non subsampled contourlet benefits to recollect the inherent organizational evidence although disintegrating and reforming the image constituents. Result grounded instructions are used for constituent replacement for image fusion. The investigations are conceded out in contradiction of the existing state of art and perceived that the projected scheme delivers auspicious outcomes pictorial and measureable. The proficiency of the projected scheme in the fused result is examined qualitatively by Isodata cataloging system.

[6] Satellite images are actuality castoff in numerous domains of exploration completed the ages. Unique of the foremost restrictions of near by these images is their determination. Thus, image determination improvement is the primary essential stage in image processing. Image determination improvement is the method of transforming the images under deliberation so that gained output image is additionally proper than the input image for essential solicitation. Image determination is imperative characteristic of any image. Improved eminence image i.e. high-determination image products improved outcomes in image processing solicitation. Determination improvement can be done in numerous fields such as spatial and transform domains. Dissimilar transform

domain approaches that are utilised for image determination improvement are viz., Discrete Wavelet transform (DWT), Stationary Wavelet Transform (SWT), Discrete Cosine Transform (DCT), Dual-Tree Complex Wavelet Transform (DT-CWT) etc. Beyond these, DT-CWT is initiate to be one of the maximum operative approaches and also examined various methods grounded on exclamation for image determination improvement. The conversation and discrimination of various transform domain approaches for image determination improvement is conceded out on satellite standard images and investigational outcomes presenting the sovereignty amongst these approaches for image resolution improvement is offered.

DWT BASED IMAGE FUSION

The input images are disintegrated into rows and columns by low-pass (L) and high-pass (H) sifting and subsequent dejected sample at particular level to obtain an approximation (LL) and aspect (LH, HL and HH) quantities. Topping purpose is connected with smooth filters or low pass filters and wavelet function with high-pass filtering. Wavelet reconditions mark accessible an structure where an image is fragmented, through individual level following to a simpler purpose band [7].

The phases complicated in the image fusion determined from wavelet transform based image fusion are given below.

- Acquire source images to perform fusion.
- Relate the wavelet transform on source images done selected wavelet at the anticipated level.
- Acquire the estimation and aspect quantities for input images.
- Combine quantities by anticipated image fusion instruction.
- Relate Inverse discrete wavelet transform on the compound quantities and obtain the final fused image.

DCT VARIANCE BASED IMAGE FUSION

Discrete cosine transform (DCT) is an significant transform broadly utilized in digital image processing [8]. Outsized DCT quantities are focused in the low frequency section; hereafter, it is recognized to have outstanding liveliness firmness possessions.

Steps involved in DCT based image fusion

- Acquire source images to be fused.
- Perform level shifting and divide input images into 8*8 blocks and accomplish the image fusion.
- Compute the 2-D DCT of 8*8 blocks and calculate normalized transform coefficients.
- Calculate Mean value of 8*8 block of images and Variance of 8*8 block of images.
- Calculate the 2-D inverse DCT of 8*8 blocks and build output fused image [9].

CONSISTENCY VERIFICATION WITH DCT VARIANCE BASED IMAGE FUSION

A common filter that can be employed in consistency verification. If the center block derives from input image B while the mainstream of the neighboring blocks originate from input image A, the center model is modestly transferred to the conforming block in input image A. The output fused image is lastly attained grounded on the reformed decision map.

In addition to steps complicated in DCT variance based image fusion the following steps are also involved.

- Compute consistency verification by means of a Main-stream Filter.
- Calculate consistency verification along with variance in DCT domain.
- Perform inverse level shifting to obtain final output image [9].

PROPOSED RESEARCH METHODOLOGY FOR SWT BASED IMAGE FUSION

The discrete wavelet transform (DWT) is absence of translation variant possession which can be abolished by expending stationary wavelet transform (SWT) is proposed. In SWT, though the signal is moved, the converted quantity will not alter and also achieves improved in denoising and edge identification. In distinction to DWT, SWT can be utilized to any subjective dimension of images rather than dimension of power of two.

Proposed SWT based methodology for image fusion is as follows

- Acquire source images to be fused.
- Image decomposition using discrete stationary wavelet transform.
- Apply fusion rule to perform image fusion.
- Utilize inverse SWT to obtain output fused image.

IMAGE DATA CHARACTERISTICS AND STRUCTURE OF PROPOSED METHOD

NRSA, Hyderabad, INDIA used IRS-1D, LISS III sensors in order to obtain images in the multispectral mode. The features of IRS 1D LISS III (image data features) are precised in Table.1

Table 1: IRS-1D LISS-III features of image Datasets used in the work

(a) Satellite/ Sensor	IRS 1D LISS 3
Image pixel resolution (spatial resolution at lowest point)	23.5 meters
Swath	127 kms (for bands 2, 3, 4) 134 kms (for band 5 – MIR)
Repetitively	25 days

Spectral Bands	0.51 – 0.58 microns (B2) 0.61 – 0.67 microns (B3) 0.76 – 0.85 microns (B4) 1.550 – 1.700 microns (B5)
----------------	---




Figure 1: The structure of the proposed method

EXPERIMENTAL RESULTS COMPILATION AND DISCUSSIONS

IRS 1D satellite and LISS-III sensor images accomplished from NRSA Hyderabad, India are compiled as input images for image fusion to obtain more informative fused images. Fused images attained from different fusion methods, DWT, DCT variance, consistency verification with DCT variance and SWT are compared. Fused outcomes are evaluated by entropy, image quality index (IQI), spatial frequency (SF), peak signal to noise ratio (PSNR), standard deviation (SD), mutual information measure (MIM) between fused image and panchromatic, fused image and multi spectral image.




Figure 2: Input image Datasets to be fused: (a),(c),(e) and (g) are MS images and (b), (d) (f) and (h) are PAN images.




Figure 3: (a), (e), (i) and (m) are DWT based fused images; (b), (f), (j) and (n) are DCT variance based fused images; (c), (g), (k) and (o) are CV combined with DCT variance based fused images and (d), (h), (l) and (p) are SWT based fused images for four Datasets.

Table 2: Assessment of Dataset 1

Assessment Parameter/ Method	DWT	DCT variance	CV with DCT variance	SWT
Entropy	7.595	7.6404	7.6478	7.80
IQI	0.999	1.0	1.0	1.0
SF	31.64	29.30	28.79	31.77
PSNR	26.12	23.18	23.87	26.84
MIM with PAN image	1.16	1.008	0.900	1.21
MIM with MS image	1.45	1.071	1.065	1.48
SD	48.87	50.16	50.38	56.85

SWT based fused image gives higher values for entropy, IQI and SD values for the Dataset 1 states that information levels, quality evidence and contrast are high for the SWT based fused image compared to DWT and DCT based fused images.

Table 3: Assessment of Dataset 2

Assessment Parameter/ Method	DWT	DCT variance	CV with DCT variance	SWT
Entropy	7.259	7.275	7.273	7.278
IQI	0.9995	1.0	1.0	1.0
SF	17.67	18.22	18.09	18.76
PSNR	26.60	24.99	25.99	26.84

MIM with PAN image	1.17	0.71	0.67	1.21
MIM with MS image	1.36	2.46	2.69	2.08
SD	38.06	38.76	39.13	39.15

SWT based fused image having better values for entropy, IQI, SF, MIM and SD in

Dataset 4 illustrates that SWT overcomes the drawbacks of other wavelet transform domains like DWT and DCT.

Table 4: Assessment of Dataset 3

Assessment Parameter/ Method	DWT	DCT variance	CV with DCT variance	SWT
Entropy	7.494	7.653	7.666	7.679
IQI	0.9988	0.9943	0.9988	0.9988
SF	32.43	37.21	31.75	19.84
PSNR	23.50	15.61	19.98	24.14
MIM with PAN image	0.9875	0.43	0.62	0.995
MIM with MS image	1.3128	0.96	1.64	1.66
SD	44.31	50.47	50.41	50.59

Potentiality of the SWT produces better values for entropy, IQI, PSNR, MIM and SD designates that SWT performs better fusion compared to other techniques discussed.

Table 5: Assessment of Dataset 4

Assessment Parameter/ Method	DWT	DCT variance	CV with DCT variance	SWT
Entropy	7.706	7.763	7.776	7.778
IQI	0.9942	0.996	1.0	1.0
SF	36.18	35.68	31.47	35.88
PSNR	19.89	16.25	20.59	21.19
MIM with PAN image	1.03	0.73	0.70	1.15
MIM with MS image	1.14	1.25	1.80	1.84
SD	53.29	55.68	56.62	56.71

As SWT will not destroy constants at each transformation level SWT based fused image having higher values for entropy, IQI, PSNR, MIM and SD indicates that SWT fusion outperforms DWT and DCT based fusion techniques.

The overall results and discussions have proved that proposed SWT based fusion techniques have met the objectives of image fusion by improving spectral and spatial information as well

CONCLUSIONS

Image fusion is a technique to converge MS and PAN images or many input images attained through different instruments into a one fused image incorporates high spectral and spatial validation. Fused images required in plentiful applications- viz image exploration, image indulgent, computer conception, cataloging, image appreciation, remote sensing, medical imaging, biometrics, video supervision. DWT, DCT and SWT image fusion approaches are implemented here. Fused results are evaluated through various assessment parameters. Because of the basic property and potentiality of the SWT based fused results outperforms DWT and DCT based fused approaches. After SWT fused results DCT variance and CV with DCT variance based fused results improved fused image content.

ACKNOWLEDGEMENT

Authors acknowledge the immense help received from the scholars whose articles are cited and included in references of this manuscript. The authors are also grateful to authors / editors / publishers of all those articles, journals and books from where the literature for this article has been reviewed and discussed.

REFERENCES

1. Saranya.G. and Nirmala Devi.S, "Performance evaluation for image fusion technique in medical images using spatial and transform method", 2016.
2. Sejal Baraiya and Lokesh P. Gagnani, "An Introduction of Image Fusion Techniques", International Journal for Innovative Research in Science & Technology, Vol. 1 No.7, 2014.
3. Tania Sultana, Md. Dulal Hossaina and Md. Karam Newaz, "Analysis on SWT based Image Fusion Techniques using Intuitionistic Fuzzy Set Operations", International Journal Of Technology Enhancements And Emerging Engineering Research, Vol. 4, No.8, pp. 16-19, 2016.
4. Rajvi Patel, Manali Rajput and Pramit Parekh "Comparative Study on Multi-focus Image Fusion Techniques in Dynamic Scene", IJCa, Vol. 109, No. 6, Pp.5-9, 2015
5. P. Mangalraj and Anupam Agrawal, "Fusion of Multi-Sensor Satellite Images using Non-Subsampled Contourlet Transform", Procedia Comput Science, Vol. 54, pp.713-720, 2015.
6. Mansing Rathod and Jayshree Khanapuri "Comparative study of transform domain methods for image resolution enhancement of satellite image", IEEE xplore, 2017.
7. D.S. Rao, M. Seetha and M.H.M. Krishna Prasad, "Quality assessment of pixel-level image fusion using fuzzy logic, IJSC, Vol. 3 No. 1, pp.13-25, 2012.
8. V.P.S Naidu, "Discrete Cosine Transform based Image Fusion Techniques, Journal of Communication, Navigation and Signal Processing", Vol. 1, No.1, pp.35-45, 2012.
9. Md. Bagher, Akbari, Aghagolzadeh and Seyedarabi, "Multi-focus image fusion for visual sensor networks in DCT domain", Journal on Computers and Electrical Engineering, Vol.37, No.5, pp.789-797, 2011.